

# Tylaska LH-Series Self-Locking Hooks

## LH Series Stainless Steel Self-Locking Hooks

- Meets CE requirements for approval as a lifting accessory.
- Fully traceable forged 17-4 PH stainless steel hook and latch.
- 100% stainless steel components.
- Dimensionally equivalent to self-locking hooks as defined in EN 1677-3:2001.
- 27% stronger than equivalent size grade 8 hooks.
- Suitable for use with Grade 80 and Grade 100 chain.
- Every hook is proof tested to 2 ½ times the working load limit.
- Fully replaceable locking mechanism.
- Available in polished stainless steel or yellow powder coated finish.



## LH Series Eye-Type Self-Locking Hooks

Model	Part Number	EN1677-3 Size Code	Chain Size (in.)	Working Load Limit (lb. [t])	Dimensions (in. [mm])								Weight (lb [g])	
					A	B	C	D	E	F	G	H		
LH8	TBD	8	5/16	5,700 [2.6]	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD
LH10	TY5010-E	10	3/8	8,800 [4.0]	1.25 [32]	6.53 [166]	1.30 [33]	4.28 [109]	0.55 [14]	1.10 [28]	1.75 [44]	2.18 [55]	4.0 [1815]	
LH13	TBD	13	1/2	15,000 [6.8]	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	TBD	

### **⚠ WARNING**

#### **LOAD DISENGAGEMENT CAN RESULT IN SERIOUS INJURY OR DEATH**

- Read and understand instructions before using hook.
- Always ensure hook and latch are closed and locked before loading hook.
- Keep hands and body from between hook and load.
- Never use tip of hook for lifting.
- Never use a damaged or excessively worn hook for lifting.
- Never exceed the hook's specified Working Load Limit (WLL).
- Never use hook in temperatures in excess of 400°F or below -30°F.
- Only use genuine Tylaska replacement parts.

